




**U2**  
MobileS

**Designed to Print on Everything**  
Introducing New U2 MobileS Ink Jet Printer

# We Got You Covered



Coated Paper




Metal & Aluminum



Hard Plastic



Flexible Plastic



Construction Materials



## U2-Mobile S Specifications

|                          |  |
|--------------------------|--|
| Display                  | 3.5" Color LCD with LED backlight  |
| LED Indicators           | Alarm, Ink low, Print, Run, Remote on/off  |
| Input Device             | Pocket-sized IR remote keypad  |
| Print Engine Technology  | Thermal Inkjet   |
| Available Languages      | English, Chinese (Traditional), Chinese (Simplified), Japanese, Russian, Korean, German, Portuguese, Spanish, French, Italian, Turkish, Hungarian, Slovak, Czech, Swedish, Romanian, Serbian Latin, Serbian Cyrillic, Bulgarian, Polish, Vietnam |
| Max. Printing Resolution | "400(h) x 600(v) dpi<br>Print quality is dependent on resolution and speed"  |
| Max. Printing Speed      | 60.96 Meters/Mins at 300 dpi setting   |
| Max. Print Distance      | Recommended 6mm from nozzle to surface   |
| Message Height           | "Up to 12.7mm (0.5")"<br>Selectable font size: 1.0mm, 1.4mm, 1.8mm, 2.7mm, 3.6mm, 4.5mm, 5.0mm, 5.5mm, 6.4mm, 8mm, 10mm, 11mm, 12.7mm"   |
| Print Capabilities       | Text, String, Logo, Shift, Counter, DateTime, Expiration Date, Barcode   |
| Barcodes                 | Code-128, ITF-14(SCC-14), NVE(SSCC-18), EAN-128, PDF417, Data Matrix, QR Code, DUN-14, GS1 Datamatrix, GS1 DataBar, GS1 DataBar EXP, GS1 QR CODE, UPCA, UPCE, EAN-13, EAN-14, EAN-8, Codabar, Aztec Code, INTER25, CODEBAR, Code-39              |
| Input/Output             | RS-485, RS-232, USB, Wi-Fi   |
| Message Storage Capacity | Store up to 999 messages   |
| Operating Temperature    | 5°C - 40°C (41°F - 104°F)  |
| Encoder                  | Embedded (400DPI)  |
| Dimensions               | 219 mm (L) x 136.9 mm (W) x 143.5 mm (H)   |
| Weight                   | 1.13kgs (2.5 lbs) excluding cartridge  |
| Standard Accessories     | Battery, battery charger with adapter, USB disk, remote control  |
| Optional Accessories     | Wi-Fi dongle, RS-485 to USB converter, Clock stabilizer  |
| PC software              | Message Pro II, Net Commander  |
| Printer Control Protocol | ANSER U2 Net Protocol  |

## Long Lasting Battery

|                                  |   |
|----------------------------------|---|
| Rated Capacity                   | 1,840 mAh   |
| Standard Voltage                 | 11.1V   |
| Charging Voltage ( Max )         | 12.6V   |
| Charging Hours ( Max )           | 2 hours   |
| Operating Temperature            | Charge: 0°C - 45°C (32°F - 113°F)<br>Discharge: -20°C-60°C (-4°F-140°F) |
| Dimensions                       | 100.3(L)x56.3 (W)x21 (H)mm  |
| Weight                           | 150g (0.33 lbs)   |
| Cycle Life                       | More than 300 cycles  |
| Continuous Printing Hours        | 4 hours   |
| Power Adapter of Battery Charger | 12.6V 2A  |
| Stand-by Time                    | 4.5 hours   |